

# MATERIAL SAFETY DATA SHEET

## TEFCOTE P3000HRX



### SECTION 1: PRODUCT IDENTIFICATION

Product Name: TEFCOTE P3000HRX PIGMENTED	Emergency Telephone Number: 01202 551212
Revision Date: 02/02/98	Product Code:

### SECTION 2: GENERAL COMPENSATION

INGREDIENT	WEIGHT %	EXPOSURE LIMIT
1. Silicone, Fluorocarbon, Anti-foam Optical Brightener	Less than 1%	N.D.
2. Propylene Glycol, Bactericides, PTFE	1 to 5%	N.D.
3. Silica, Wax Emulsion, Flame Retardant	1 to 5%	N.D.
4. Di Butyl Ester	1 to 5%	OES-STEL = 10mg/m <sup>2</sup> (H.S.E)
5. Butyl Diglycol, Titanium Dioxide	5 to 15%	N.D.
6. Polyurethane Dispersion	5 to 15%	N.D.
7. Acrylic Polymer	15 to 30%	N.D.
8. Water	Over 30%	N/A.

### SECTION 3: HAZARDS IDENTIFICATION

Little hazard in normal use.
------------------------------

### SECTION 4: FIRE AID MEASURES

Ingestion:	Seek medical attention. Drink plenty of water.
Inhalation:	Remove to fresh air.
Eye Contact:	Flood with water. Seek medical attention if irritation persists.
Skin Contact:	Wash with soap and water.

### SECTION 5: FIRE FIGHTING MEASURES

Suitable Extinguishing Media:		Non inflammable. Polymer can burn following evaporation of Water. Wear self contained breathing Apparatus and full protective gear.
Extinguishers to Avoid:		
Special Fire/Gas Hazards:		
Special Exposure Hazards Fire/Gas:		
Protective Equipment for Fire Fighters:		

### SECTION 6: ACCIDENTAL RELEASE MEASURES

Disposal Considerations:	Minor: Wash to drain. Major: Contain in sand or earth, dispose of by land infill.
Exposure Controls/Personal Protection:	Wear overalls and impervious gloves

**SECTION 7: HANDLING AND STORAGE**

<b>Storage Temperatures:</b>	Avoid temperature extremes. Do not allow to freeze.
<b>Maximum Stacking Height:</b>	Only stack in cartons provided with product and not more than 4 high.
<b>Special Requirements:</b>	None.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

<b>Respiratory Protection:</b>	Keep well ventilated.
<b>Hand Protection:</b>	Wear impervious gloves.
<b>Eye Protection:</b>	Wear safety glasses if likely to splash in face.
<b>Skin Protection:</b>	Wear overalls.

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

<b>Appearance/Odour:</b> Viscous pigmented Liquid	<b>Specific Gravity:</b> 1.14
<b>Ph:</b> 7.5	<b>Solubility:</b> Fully water missible
<b>Flash Point:</b> N/A	

**SECTION 10: STABILITY AND REACTIVITY**

<b>Conditions to Avoid:</b>	Extremes of Temperature. Has a shelf life of 1 year.
<b>Materials to Avoid:</b>	Do not mix with other chemicals.

**SECTION 11: TOXICOLOGY INFORMATION**

<b>Route of Exposure:</b>	Effects.
<b>Inhalation:</b>	Use in poorly ventilated areas may lead to dizziness. Remove to air.
<b>Ingestion:</b>	Drink water and seek medical aid.
<b>Skin Contact:</b>	Wash with plenty of water, if irritation persists seek medical advice.
<b>Eye Contact:</b>	Flush with water for 15 minutes. If irritation persists seek medical advice.

**SECTION 12: ECOLOGICAL INFORMATION**

<b>Degradability/Aquatic Toxicity:</b>	Little danger to the environment in normal use.
--	---

**SECTION 13: DISPOSAL CONSIDERATIONS**

<b>Special Disposal Instructions:</b>	Not applicable.
---------------------------------------	-----------------

**SECTION 14: TRANSPORT INFORMATION**

<b>Special Transport Precautions:</b>	Little hazard in transport.
---------------------------------------	-----------------------------

**SECTION 15: REGULATORY INFORMATION**

<b>Requirements under CHIP Regs:</b>	Little hazard associated with this product.
N.B. The information contained in this data sheet does not constitute a users assessment of workplace risks.	

**SECTION 16: OTHER INFORMATION**

<b>Training Advice:</b>	The British Institute of Cleaning Science, offer excellent additional advice
<b>Recommended Uses:</b>	Polyurethane/Acrylic emulsion wall paint.